

FOURflex
IP65 Flexible LED Strip



Technical Data Sheet

FOURflex IP67 Flexible LED Strip

- IP67, UV stabilised Flexible LED
- Factory sealed front, side or bottom entry injection molded feeds
- Available in both Horizontal and Vertical bending radius
- 2700k, 3000k, 3500k & 4000k (RGB on Request)
- Custom mounting accessories
- Supplied with remote 24vDC (Non-dim, 1-10v or DALI) power supply



OPTIONS

BF-F10VB	BF-F15HB	BF-F16VB	BF-F21HB
<p>F10A-ALU</p>	<p>F15/F21</p>	<p>F16</p>	<p>F15/F21</p>



Technical Data Sheet

TECHNICAL PARAMETERS

BF10-VB	BF15-HB	BF16-VB	BF21-HB
IP67	IP67	IP67	IP67
24vDC	24vDC	24vDC	24vDC
*10w (m)	*12w (m)	*12w (m)	*12w (m)
*320lm (m)	*320lm (m)	*480lm (m)	*320lm (m)
27/30/35/4000k	27/30/35/4000k	27/30/35/4000k	27/30/35/4000k

*approx. based on 4000k, refer to photometric data for more details.

SPECIFICATION CONFIGURATOR - example below

PRODUCT	FOURFLEX	BF15-HB	3000K	1-10V	8000MM
FOURFLEX					<div style="border: 1px solid black; padding: 5px; width: fit-content; margin: auto;"> <p><i>Cutting increments (x-mm) up to (x-mm) per driver</i></p> </div>
VERSION					
BF10-VB					
BF15-HB					
BF16-VB					
BF21-HB					
CCT					
2700K					
3000K					
3500K					
4000K					
CONTROLS					
NON-DIM					
1-10V					
DALI					