

B4 FOURflat

LED Panel | Office Compliant | Dimmable | UGR19



B4 FOURflat Low Glare LED Panel

- CRI80+
- Available in 4000k
- 4000lm, 38W 1050mA | 2700lm, 21W 700mA
- 3-Step MacAdam binning, L70 @ 50,000h
- UGR19 - 38W | UGR17 - 21W

B4-6060 - 595mmx595mm	B4-12030 - 1195mmx295mm	B4-FF-SKIT - suspension kit	B4-FF-MFR - mounting frame

Technical Data Sheet - Low Glare LED Panel

SPECIFICATION CONFIGURATOR

PRODUCT CODE	B4-FF - 6060 - 38 - 840 - U - ND
6060 - 600 x 600 LED Panel	
12030 - 1200 x 300 LED Panel	
POWER OUTPUT	
38 - 38w @ 1050mA	
21 - 21w @ 700mA	
COLOUR TEMP	
840 - 4000K	
UGR	
U - low glare	
CONTROL GEAR	
ND - remote non dim power supply	
PD - remote phase dim power supply	
1-10V - remote 1-10v power supply	
DALI - remote DALI power supply	

B4-FF-6060-38-840-U-ND

B4 FOURflat 600 x 600mm 4000K CRI80 LED Panel, office compliant, constant current 38w 1050mA 3800lm UGR19 c/w remote non dim power supply.

ACCESSORIES
SKIT - suspension kit
MFR6060 - mounting frame 600x600
MFR1230 - mounting frame 1200x300

B4-FF - SKIT

B4-FF-SKIT

B4 FOURflat LED Panel Suspension Kit